

Helping Make Safe & Reliable Products
Because people count on your products everyday



CSZ
Cincinnati Sub-Zero

**CONSTANT CLIMATE
REACH-IN CHAMBERS**



www.cszproducts.com

Constant Climate Chambers

Our chambers are ideal for ICH Q1A stability testing, shelf life, package testing and accelerated aging.



Keeping your products on schedule allows you to deliver life-saving products to patients sooner. We understand the importance of having reliable and stable chambers to ensure tests are completed in a timely manner while complying with regulatory standards.

Whether your testing is for R&D, clinical trials or ongoing stability, our chambers and rooms provide uniform temperature/ humidity conditioned environments for worry-free operations with a control system that is easy to use and saves time.

Stability Chambers are used for a variety of test applications including:

- Packaging
- Medical Devices
- Personal Care Products
- Consumer Products
- Research





Constant Climate Chambers

StableClimate® II

Constant Climate Chambers

Our chambers provide a stable, temperature and/or humidity-conditioned environment for worry-free operation with a control system that is easy to use and saves you time. These chambers are available in temperature or temperature and humidity models with three different chamber sizes in a single, double or triple door configuration. Validation protocol is included upon request. Factory trained service group also provides onsite validation. Below are some of the key features & benefits included.

Features



- Broad temperature & humidity range from +2°C to +70°C to meet a variety of test and storage conditions for more versatility.
- Superb CSZ EZT-570 21 CFR Part 11 Compliant touch-screen controller with automated humidity control dehumidification and manual or automatic user settings for defrost.
- Ethernet connectivity to remotely monitor and control your chamber using VNC.
- EIA-485 & EIA-232 computer interface for communications with software and the ability to control multiple chambers.
- Full heated glass doors with lock keep your product secure and provide product viewing.
- Cabinet is insulated with CFC-free polyurethane foam for thermal protection. Finish consists of durable white power-coated exterior and corrosion resistant stainless steel interior.
- Solid stainless steel shelves slide out for convenience. Shelves are easy to clean, install and relocate. Three shelves per door are included and additional shelves are available
- 2" cable port for temperature monitoring or mapping.
- Compact size and casters allow you to move the chamber throughout your lab with leveling legs to secure and level your chamber.
- Single door model 115V and plug into standard 20 amps electrical outlet for easy installation.
- IQ, OQ, PQ protocol included. On-site validation is optional.

Constant Climate Chambers

Precise Uniformity

Horizontal air flow design directs air across the chamber and solid shelves assuring consistent air flow for better uniformity with faster temperature recovery from door openings. Top to bottom air flow designs can restrict air movement and cause "dead spots" of air in the chamber and other designs which circulate front to back can cause temperature recovery after door openings to be longer.

These chambers are used to test and store a wide range of products in specific temperature and/or humidity conditions.



Optional Accessories


- Low Humidity
- Recirculating Water
- UV Recirculating Water
- Opaque Door
- Chart Recorder
- LED Light
- Additional Shelves
- Duplex Outlet
- Additional Ports
- Water Demineralizer System
- Reverse Osmosis Water System
- UPS Backup for Controller





StableClimate® II Specifications

	ST(H)-24	ST(H)-52	ST(H)-82
Workspace	24 cu. ft. (680L)	52 cu. ft. (1473L)	82 cu. ft. (2322L)
Temperature Range	+2°C to +70°C		
Humidity Range	20% to 95% RH		
Internal Dimensions	24.5"W x 28"D x 60.5"H (62cm x 71cm x 154cm)	54"W x 28"D x 60.5"H (137 cm x 71cm x 154cm)	84"W x 28"D x 60.5"H (213cm x 71cm x 154cm)
External Dimensions	33"W x 35"D x 90"H (84cm x 89cm x 229cm)	65"W x 35"D x 90"H (165 cm x 89cm x 229cm)	97"W x 35"D x 91.2"H (246cm x 89cm x 231.6cm)
Temperature Tolerance¹	±0.3°C		
Temperature Uniformity¹	±1°C (±0.6°C from 25°C to 50°C)		
Humidity Tolerance¹	±3%		
Humidity Uniformity¹	±4%		
Maximum Shelf Weight	75 lbs. (34 kg) per shelf		
Standard Shelves	3 Shelves	6 Shelves	9 Shelves
Maximum Shelves	10 Shelves	20 Shelves	30 Shelves
Heat of Rejection ²	1055 watts (3,600 BTU/hr) maximum during cooling operation	2460 watts (8,400 BTU/hr.) maximum during cooling operation	3253 watts (11,100 BTU/hr) maximum during cooling operation
Maximum Weight Capacity	300 lbs. total (136 kg)	600 lbs. total (272 kg)	900 lbs. total (408 kg)
Voltage Breaker Size	115V/1Ph/60Hz 20 amp minimum service	230V/1Ph/60Hz 30-amp minimum service ³	



¹ Control derived from the deviation of the temperature control sensor from the set point. Uniformity derived from the maximum deviation of 9 temperature sensors placed on 3 horizontal planes across entire temperature range at 24°C ambient.
² Integral air-cooled models require an ambient temperature range between +21.1°C (+70°F) TO +26.7°C (+80°F) for proper operation and performance.
³ Customer to supply power cord and plug.



The Next Generation Controller with Smartphone Technology

Communications & Connectivity

- Remotely monitor and/or Control the chamber for anytime, anywhere access from any device (PC, smartphone or tablet) using LAN/VNC.
- Alarm notification system sends email and/or text phone messages in the event of a test chamber alarm, saving valuable tests while reducing downtime.
- Multiple chambers may also be managed using VNC or CSZ's optional EZ-View PC software to monitor control CSZ chambers and download profiles.
- Ethernet TCP/IP, EIA-232, EIA-485 Communications



Save valuable time with the ease of use of the EZT-570 featuring fewer steps to accomplish your daily testing needs while incorporating simplified operation and programming to test faster.



Profiling

- Profiling includes up to 99 steps and 1000 cycles.
- Program ramp steps entering time or °C/min.
- Easily review profile using trend chart or list of steps
- Profile status view displays current step, estimated start/stop date and time.
- Profiles may be transferred to different chambers via USB or optional EZ-View software.




Data Logging

- Configurable log interval, data file length, filename, operator entered batch & lot information as well as an unlimited number of operator notes saved to the data file.
- Easily download profiles, alarm files, audit trail files and data files using USB or email from controller in a compatible .csv file format.
- Files may also be automatically backed up daily for hassle-free file management using FTP. FTP/FileWeb/DataWeb (LAN/WAN).
- Email built-in to send data, alarm, audit trail files directly from controller. Also create and send new emails.
- Open and plot historical data files.



User Convenience & Flexibility

- Controller may be configured in any of one of 28 languages- one setting updates icons, menus and help screen.
- Selectable power failure/recovery options.
- Full system security allows up to 30 different users with four different levels of security.
- Audit trail files track changes in settings by each user.
- Import/export configuration settings to other controllers saving time. (Personalized to your use)
- Configurable alarms and maintenance alerts.





Cincinnati Sub-Zero is a product brand of Weiss Technik North America, Inc. Weiss Technik North America is a member of the Weiss Technik group of companies, a division of the Schunk Group with its headquarters in Heuchelheim, Germany. Weiss Technik is the world's largest manufacturer of environmental simulation systems and employs more than 2,900 people in 18 group companies in 15 countries.

[Request Information](#)

Additional life science solutions are available.

- Photostability Testing
- BioStore Freezer Rooms
- PharmaEvent Stability Testing



CSZ
Cincinnati Sub-Zero
The Testing Standard.

Weiss Technik North America, Inc.
Cincinnati Facility
12011 Mosteller Road
Cincinnati, OH 45241

(p) **513-326-5252**
(f) **513-326-5258**

www.cszproducts.com

