

Model	Blower Capacity		Net Cooling Capacity in BTU's/Hr.			
	HP	CFM	-18°C	-34°C	-40°C	-54°C
RC-Series						
Single Stage						
RC-308-2	1	300	4,420	800	-	-
RC-308-3	1	300	7,345	1,000	-	-
RC-816-6	3	800	11,840	4,500	-	-
RC-832-7.5	3	800	23,800	9,400	-	-
RC-864-10	3	800	34,850	14,880	-	-
RC-864-15	3	800	44,900	20,950	-	-
Cascade						
RC-308-2-2	1	300	-	-	2,380	1,700
RC-308-3-3	1	300	-	-	7,200	4,600
RC-816-6-6	3	800	-	-	12,000	7,000
RC-832-7.5-7.5	3	800	-	-	17,000	9,720
RC-864-10-10	3	800	-	-	37,000	20,000
RC-864-15-15	3	800	-	-	47,000	30,000
ZPRC-Series						
Single Stage						
ZPRC-16-3.5	1	300	8,520	-	-	-
ZPRC-16-6	1	300	10,578	-	-	-
ZPRC-32-3.5	1	300	8,530	-	-	-
ZPRC-32-6	1	300	10,578	-	-	-
ZPRC-32-10	3	800	18,767	-	-	-
ZPRC-32-15	3	800	25,591	-	-	-
ZPRC-44-3.5	1	300	7,848	-	-	-
ZPRC-44-6	1	300	9,554	-	-	-
ZPRC-44-10	3	800	18,767	-	-	-
ZPRC-44-15	3	800	25,591	-	-	-
ZPRC-64-3.5	1	300	7,165	-	-	-
ZPRC-64-6	1	300	8,872	-	-	-
ZPRC-64-10	3	800	18,767	-	-	-
ZPRC-64-15	3	800	25,591	-	-	-
Cascade						
ZPRC-16-6-6	1	300	-	-	8,530	6,483
ZPRC-32-6-6	1	300	-	-	8,530	6,483
ZPRC-32-10-10	3	800	-	-	13,649	10,236
ZPRC-32-15-15	3	800	-	-	17,061	13,649
ZPRC-44-6-6	1	300	-	-	7,507	5,459
ZPRC-44-10-10	3	800	-	-	13,649	10,236
ZPRC-44-15-15	3	800	-	-	17,061	13,649
ZPRC-64-6-6	1	300	-	-	6,824	5,459
ZPRC-64-10-10	3	800	-	-	13,649	10,236
ZPRC-64-15-15	3	800	-	-	17,061	13,649

Performance based on 60 Hz. Temperature only operation and 24°C ambient air. If ambient temperature exceeds 30°C, CSZ recommends a water cooled condenser. For 50 Hz. Operation, stated performance and air flow will be approximately 17% less. The addition of live load will affect humidity control. Specifications are subject to change.

