


Announcing the **NEW** ZP Express Program



Receive our most popular ZP temperature and/or humidity chambers in just 6-8 weeks. You can even select from common options listed below.

Applicable Models

Single Stage: -34°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Cascade: -70°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Tundra: -45°C to +190°C 208/230V, 3 Ph, 60 Hz.
Temperature Chambers ZPE-8-2-SC/AC ZPE-16-2-SC/AC ZPE-32-2-SC/AC	Temperature Chambers ZPE-8-2-2-SC/AC ZPE-16-2-2-SC/AC ZPE-32-2-2-SC/AC	Temperature Chambers ZPE-8-3.5-SCT/AC ZPE-16-3.5-SCT/AC ZPE-32-3.5-SCT/AC
Temperature/Humidity Chambers ZPHE-8-2-SC/AC ZPHE-16-2-SC/AC ZPHE-32-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-2-2-SC/AC ZPHE-16-2-2-SC/AC ZPHE-32-2-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-3.5-SCT/AC ZPHE-16-3.5-SCT/AC ZPHE-32-3.5-SCT/AC

Options Available

- Recirculating water option
- Demineralizer cartridge
- Rear top vent exhaust
- Sound deadening
- Shelves
- Low humidity
- Product High/Low Limit
- Dry air purge system
- LN2 boost
- Water pressure regulator
- Reverse osmosis
- EZ View
- Extended warranty



Notes:

Shipping 6-8 weeks from order acknowledgment
 Please consult factory for quantity orders of the same model
 Not applicable to 50 Hz. Models

