


Announcing the **NEW** ZP Express Program



Receive our most popular ZP temperature and/or humidity chambers in just 2-4 weeks. You can even select from common options listed below.

Applicable Models

Single Stage: -34°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Cascade: -70°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Tundra: -45°C to +190°C 208/230V, 3 Ph, 60 Hz.
Temperature Chambers ZPE-8-2-SC/AC ZPE-16-2-SC/AC ZPE-32-2-SC/AC	Temperature Chambers ZPE-8-2-2-SC/AC ZPE-16-2-2-SC/AC ZPE-32-2-2-SC/AC	Temperature Chambers ZPE-8-3.5-SCT/AC ZPE-16-3.5-SCT/AC ZPE-32-3.5-SCT/AC
Temperature/Humidity Chambers ZPHE-8-2-SC/AC ZPHE-16-2-SC/AC ZPHE-32-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-2-2-SC/AC ZPHE-16-2-2-SC/AC ZPHE-32-2-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-3.5-SCT/AC ZPHE-16-3.5-SCT/AC ZPHE-32-3.5-SCT/AC

Options Available

- | | |
|------------------------------|----------------------------|
| • Customer event | • Low humidity |
| • Digital Input/output | • Dry air purge system |
| • Recirculating water option | • LN2 boost |
| • Demineralizer cartridge | • Water pressure regulator |
| • Rear top vent exhaust | • Reverse osmosis |
| • Sound deadening | • EZ-View |
| • Shelves | • Extended warranty |



Notes:

Shipping 2-4 weeks from order acknowledgment
 Please consult factory for quantity orders of the same model
 Not applicable to 50 Hz. Models

Weiss Technik North America, Inc.
 Cincinnati Facility
 12011 Mosteller Road
 Cincinnati, OH 45241
 (p) 513-326-5252
 (f) 513-326-5258
www.cszindustrial.com

CSZ
Cincinnati Sub-Zero
The Testing Standard.